



ASSEMBLY	BELT TYPE	TEMPERATURE RANGE °C		WORKING LOAD (MAX.)	BACKFLEX RADIUS (MIN.)
		DRY	WET	N/M (21 °C)	MM
LFAG (LOW FRICTION ACETAL GREY) - WITH PBT PINS					
FLOW BACK PRESSURE (LBP)	2540/1005-LBP-LFAG-M***	-40 TO 82	-40 TO 66	22000	25

M*** IN CODE NUMBERS CORRESPONDS WITH THE BELT WIDTH (W) IN MM, REFER TO ADDITIONAL BELT WIDTH TABLE FOR STANDARD WIDTHS (W) AND CORRESPONDING CODES.

WIDTH W	ASSEMBLY : LOW BACK PRESSURE WITH ROLLERS	
MM	CODE	LFAG (GREY)
85	E00008B-A6-C1-00001	2540/1005-LBP-LFAG-M0085
170	E00008B-A6-C1-00002	2540/1005-LBP-LFAG-M0170
255	E00008B-A6-C1-00003	2540/1005-LBP-LFAG-M0255
340	E00008B-A6-C1-00004	2540/1005-LBP-LFAG-M0340
425	E00008B-A6-C1-00005	2540/1005-LBP-LFAG-M0425
510	E00008B-A6-C1-00006	2540/1005-LBP-LFAG-M0510
595	E00008B-A6-C1-00007	2540/1005-LBP-LFAG-M0595

OTHER WIDTHS AVAILABLE ON REQUEST. STANDARD ORDER QTY: PER METER



120 ROWS
(3,048M)



SPROCKETS/IDLERS
PG. F10 - F11



CURVES/BENDS
PG. G5-G6



MATERIALS



TABLE OF
CONTENTS



BACK TO MODULAR
BELT INDEX (E)